

660ESD



CARE INSTRUCTION

- Good resistance to the majority of chemical substances.
- Allows both dry and greasy parts to be gripped effectively
- Free of substances that are currently known to cause allergies
- The antistatic properties will only function when the gloves are used with other antistatic equipment (clothing, shoes...)
- Store dry and cool sheltered from direct light.

MATERIAL

Liner:
Cotton, Polyester, Other

Coating:
PVC

COUNTRY OF ORIGIN

Malaysia

PACKAGING

1 pair in a bag
60 pairs in a carton

SIZE

9/L 10/XL

STANDARDS

89/686/EEC **CE0120**
CAT.III

EC Type Examination Certificate
From SGS United Kingdom Ltd.,
202B Worle Parkway,
Weston-super-Mare, BS22 6WA, UK
Notified Body No.0120

EN 420:2003

Dexterity
Level 5
(Min.1 - Max.5)

EN 388:2003



4 1 2 1

Mechanical risks

Abrasion (Min.0 - Max.4)	4
Cut (Min.0 - Max.5)	1
Tear (Min.0 - Max.4)	2
Puncture (Min.0 - Max.4)	1

EN 374-2:2003



Penetration

Level2 Inspection level G1 AQL: <1.5
(Min.1 - Max.3)

EN 374-3:2003



A J K L

Permeation

A: Level 3 Methanol - CAS No.67-56-1
J: Level 3 n-Heptane - CAS No.142-82-5
K: Level 6 Sodium hydroxide 40% - CAS No.1310-73-2
L: Level 4 Sulphuric acid 96% - CAS No.7664-93-9
(Min.0 - Max.6)

EN 1149-1:1996

Surface resistivity

Face surface
6.1 x 10⁸ (Ω)

Reverse surface
3.2 x 10⁸ (Ω)

