

B0710



CARE INSTRUCTION

- Do not use where there are electrical, thermal or entanglement risks.
- Store in a dry place, away from the light.
- Discard used gloves in compliance with local regulations.
- Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance.

MATERIAL

PVC

COUNTRY OF ORIGIN

Malaysia

PACKAGING

1 pair in a bag
100 pairs in a carton

SIZE

7/S 8/M 9/L 10/XL

STANDARDS

89/686/EEC

CE0120
CAT.III

EC Type Examination Certificate
From SGS United Kingdom Ltd.,
202B Worle Parkway,
Weston-super-Mare, BS22 6WA, UK
Notified Body No.0120

EN 420:2003

Dexterity
Level 5
(Min.1 - Max.5)

EN 388:1994



3 0 0 0

Mechanical risks

Abrasion (Min.0 - Max.4)	3
Cut (Min.0 - Max.5)	0
Tear (Min.0 - Max.4)	0
Puncture (Min.0 - Max.4)	0

EN 374-2:1994



Penetration

Level 3 Inspection level G1 AQL: <0.65
(Min.1 - Max.3)

EN 374-3:1994



Permeation

Level 2 Hydrochloric acid 36% - CAS No.7647-01-0
Level 6 Sodium hydroxide 40% - CAS No.1310-73-2
Level 2 Kerosene
Level 0 Methanol - CAS No.67-56-1
(Min.0 - Max.6)

