

350R



CARE INSTRUCTION

- Glove knitted from cotton and polyester.
- Nitrile Butadiene Rubber coating on the palm, under the fingers and on the last phalange on the back of the finger.
- The glove protects against mechanical risks.
- Do not use where there are chemical, electrical or thermal risks.
- Because of their high traction resistance, do not use these gloves when there is a risk of them being caught up in moving machinery.
- The glove does not contain any substances at rates that are known or suspected to have harmful consequences on the hygiene or the health of the user under foreseeable using conditions.
- Store in a dry place, away from the light.
- Wash at 40°C max with neutral detergent.
- No change in EN388 test performance after 3 wash cycles, however, in-service performance may differ.

MATERIAL

Liner:
Polyester, Cotton, Other

Coating:
Nitrile

COUNTRY OF ORIGIN

Vietnam


PACKAGING

1 pair in a bag
120 pairs in a carton

SIZE

7/S 8/M 9/L 10/XL

STANDARDS

89/686/EEC  EC Type Examination Certificate from IFTH
Avenue Guy de Collongue,
69134 Ecully Cedex, France
Notified Body No. 0072

EN 420:2003+A1:2009

Dexterity
Level 5
(Min.1 - Max.5)

EN 388:2003



4 2 3 1

Mechanical risks

Abrasion (Min.0 - Max.4)	4
Cut (Min.0 - Max.5)	2
Tear (Min.0 - Max.4)	3
Puncture (Min.0 - Max.4)	1

