

KV660



CARE INSTRUCTION

- Do not use where there are electrical, thermal or entanglement risks.
- Store in a dry place, away from the light.
- Discard used gloves in compliance with local regulations.
- Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance.

MATERIAL

Liner:
Aramid, Polyester, Other

Coating:
PVC

COUNTRY OF ORIGIN

Malaysia

PACKAGING

1 pair in a bag
60 pairs in a carton

SIZE

8/M 9/L 10/XL 11/XXL

STANDARDS

89/686/EEC **CE0120**
CAT.III

EC Type Examination Certificate
From SGS United Kingdom Ltd.,
202B Worle Parkway,
Weston-super-Mare, BS22 6WA, UK
Notified Body No.0120

EN 420:2003+A1:2009

Dexterity
Level 5
(Min.1 - Max.5)

EN 388:2003



4 3 4 2

Mechanical risks

Abrasion (Min.0 - Max.4)	4
Cut (Min.0 - Max.5)	3
Tear (Min.0 - Max.4)	4
Puncture (Min.0 - Max.4)	2

EN 374-1:2003



J K L

Permeation

J: Level 3 n-Heptane - CAS No.142-82-5
K: Level 6 Sodium hydroxide 40% - CAS No.1310-73-2
L: Level 2 Sulphuric acid 96% - CAS No.7664-93-9
(Min.0 - Max.6)

EN 374-2:2003



Penetration

Level 2 Inspection level G1 AQL: <1.5
(Min.1 - Max.3)

