

# 620



## CARE INSTRUCTION

- Do not use where there are electrical, thermal or entanglement risks.
- Store in a dry place, away from the light.
- Discard used gloves in compliance with local regulations.
- Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance.

## MATERIAL

**Liner:**  
Cotton, Polyester, Polyurethane

**Coating:**  
PVC

## COUNTRY OF ORIGIN

Malaysia

## PACKAGING

1 pair in a bag  
60 pairs in a carton

## SIZE

8/M 9/L 10/XL 11/XXL

## STANDARDS

89/686/EEC **CE0120**  
CAT.III

EC Type Examination Certificate  
From SGS United Kingdom Ltd.,  
202B Worle Parkway,  
Weston-super-Mare, BS22 6WA, UK  
Notified Body No.0120

### EN 420:2003+A1:2009

Dexterity  
Level 5  
(Min.1 - Max.5)

### EN 388:2003



3 1 2 1

### Mechanical risks

|                                |   |
|--------------------------------|---|
| Abrasion (Min.0 - Max.4) ..... | 3 |
| Cut (Min.0 - Max.5) .....      | 1 |
| Tear (Min.0 - Max.4) .....     | 2 |
| Puncture (Min.0 - Max.4) ..... | 1 |

### EN 374-1:2003



### Permeation

J: Level 1 n-Heptane - CAS No.142-82-5  
K: Level 6 Sodium hydroxide 40% - CAS No.1310-73-2  
L: Level 2 Sulphuric acid 96% - CAS No.7664-93-9  
(Min.0 - Max.6)

### EN 374-2:2003

### Penetration

Level 1 Inspection level S4 AQL: <4.0  
(Min.1 - Max.3)

